

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau(43) International Publication Date  
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number  
**WO 2004/018775 A1**(51) International Patent Classification<sup>7</sup>: **E01C 23/088**,  
23/14, 23/08(21) International Application Number:  
PCT/IL2003/000690

(22) International Filing Date: 20 August 2003 (20.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
151353 20 August 2002 (20.08.2002) IL(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and


(72) Inventor: **MANOR, Zamir** [IL/IL]; Hapsanter 11/18,  
75583 Rishon Le-Zion (IL).(74) Agent: **REINHOLD COHN AND PARTNERS**; P. O.  
BOX 4060, 61040 Tel Aviv (IL).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR ERASING ROAD LANE MARKINGS



(57) Abstract: An apparatus for erasing a road marking on a road lane comprising a chassis adapted to travel over the road lane; a heating source mounted to the chassis for directly or indirectly applying heat to the road marking; and a positively driven rotatable brush mounted to the chassis. The brush has bristles contactable with the road marking and adapted for removing it, when heated, from the road. Indirect heating of the road marking can be accomplished by first heating the bristles of the brush.

## APPARATUS AND METHOD FOR ERASING ROAD LANE MARKINGS

### 5 FIELD OF THE INVENTION

The present invention relates to an apparatus and method for removing road markings such as lane lines, stripes, arrows and the like from roads.

### BACKGROUND OF THE INVENTION

Road lane markings, such as lane lines, stripes, arrows and the like are  
10 commonly applied to road lanes for designating vehicular traffic flow.

Large efforts have been expended to improve the durability of these road markings in the face of intensive wear caused by vehicle tires and deterioration caused by the sun and weather. Hence, there have been a variety of marking substances (special paints, heated thermosetting or reactive thermoplastics, epoxy  
15 and other materials) developed and introduced.

Techniques have also been developed to increase the thickness of the applied paint layer composing the markings, so that it will be felt by drivers when passed over and to produce reflecting effects to increase the ease and safety of night-time driving.

20 Occasionally there exists the need to erase existing road markings. This may occur when the road undergoes maintenance operations, changes such as the addition of a lane or lanes, temporary deviations or detours, or other circumstances requiring the erasure of road markings.

A typical method to eliminate the markings is simply to cover them with a  
25 layer of pitch. However, this cover material can prove to be reflective when illuminated by vehicle headlights, which of course is confusing and uncomfortable for the driver and may cause a traffic safety problem. If the

- 2 -

markings are chipped off (e.g. with chisels or by sand blasting), the result will be the formation of cavities or depressions that may endanger driving and damage vehicles.

## SUMMARY OF THE INVENTION

5       The present invention relates to an apparatus and method for removing road markings such as lane lines, stripes, arrows and the like (hereinafter in the specification and claims, "*road markings*"), from roads the apparatus comprising a chassis adapted to travel over the road lane; a heating source mounted to the chassis for directly or indirectly applying heat to the road marking; and a  
10       positively driven rotatable brush mounted to the chassis. The brush has bristles contactable with the road marking and adapted for removing the road marking, when heated, from the road.

The method for removing road markings from roads comprises:

- 15       - providing an apparatus comprising a chassis with a heating source and a rotatable brush mounted thereto, the brush having bristles;
- bringing the apparatus to the road lane;
- causing the chassis to travel over the road lane;
- applying heat directly or indirectly to the road marking; and
- 20       - causing the bristles of the brush to rotate and contact the road marking thereby removing the marking.

The chassis is typically adapted for mounting or attaching to the front of a truck or other suitable vehicle. Mounting to the front of the truck aids visibility of the markings to be removed, however, the apparatus can be designed for rear  
25       mounting or even mounting such that at least the bulk of the apparatus is disposed to the side of the truck.

It is preferable that the apparatus comprises a means to displace the chassis, or at least the brush, in a direction transverse to the truck, to facilitate alignment of the brush with the markings. Alternatively, the apparatus may be

- 3 -

designed in a simpler manner wherein it does not include such means to displace the brush or chassis and the appropriate alignment of the brush with the markings is obtained by appropriately positioning the truck controls.

### BRIEF DESCRIPTION OF THE DRAWINGS

5        These and additional constructional features and advantages of the invention will become more clearly understood in the light of the ensuing descriptions of embodiments thereof, given by way of example only with reference to the accompanying drawings, wherein:

**Fig. 1** is a schematic side view of an apparatus and associated vehicle for  
10 removing road markings according to the present invention;

**Fig. 2** is a top view of the apparatus in Fig. 1;

**Fig. 3** is a bottom view of the apparatus of Fig. 1, on an enlarged scale;

**Fig. 4** is a view in the direction of arrow IV in Fig. 2, on an enlarged scale;

15        **Fig. 5** is a schematic side view of another embodiment of the apparatus according to the present invention; and

**Fig. 6** is a view in the direction of arrow VI in Fig. 5.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

      Schematically shown in Figs. 1 and 2 is a vehicle 10, generally of any  
20 conventional type, e.g. a small truck, the vehicle adapted however to allow the attachment (e.g. mounting, connecting) thereto of an apparatus 12 designed for removing or erasing road markings M from a road R. The apparatus 12 is shown mounted to the front of the vehicle 10 by a pair of brackets 14 and 16.

      The apparatus 12, as a whole, is mounted to the brackets 14 and 16 by  
25 both a cross shaft 18 and a screw-threaded spindle 20, best seen in Fig. 4, extending parallel to each other. The apparatus 12 is thus suspended above the road R, in cantilever fashion, carried by horizontal chassis side rails 22, 24 rigidly connected to vertical rails 26 and 28 (Fig. 4). Rails 26 and 28 are coupled

- 4 -

to the shaft 18 by slide bearings 30 and 32 and to the spindle 20 by nuts 34 and 36, respectively.

Alternatively, the apparatus 12 could be adapted to be at least partially supported above the road R by means other than, or in coordination with, the cantilever type arrangement detailed herein above. One such means is the use of any number of wheels (not shown) to allow the apparatus 12 to ride over the road R. By one aspect of this alternative, the weight of the apparatus 12 could be supported by these wheels in conjunction with the brackets 14 and 16 to support the apparatus. By another aspect, the weight of the apparatus 12 could be completely supported by wheels.

If the apparatus 12 were completely supported by wheels, the attaching arrangement need merely be a connecting mechanism to allow pushing (or pulling) thereof, and need not be a load bearing mechanism such as mounting.

With reference to Figs. 1 and 3, the apparatus 12 is further provided with a heating source 50 such as a multi-flame burner unit having torches 51. The heating source 50 is suspended from above (although alternatively, it may be supported from below), and adjustably movable by an assembly comprising a pneumatic cylinder 52 and a piston 54 mounted to a top rail 56, guided by rollers 58, 60 along vertical rails 62, 64 respectively. A chimney fitting tube 66 extends upward into a chimney 68 to enable up and down movement of the heating source 50.

Alternatively the heating source could be, for example, an electric forced air heater (not shown) powerable by the vehicle's battery or another source of electricity.

As seen best in Fig. 4, the apparatus 12 can be transversely moved from side to side by rotation of the spindle 20 while maintaining an essentially constant height above the road R. The spindle 20 may be rotated in either or both directions by known means such as an electric drive motor 38 coupled thereto by sprocket wheels 40 and 42 via a sprocket chain 44.

- 5 -

A supply line 70, at least a portion of which is helically configured, is provided for flowing combustible gas or liquid (e.g. butane, propane, natural gas, kerosene etc.) from gas containers 72 carried by the vehicle 10 (Fig. 1). The helical configuration allows for movement of the heating source 50 and an analogous configuration (not seen) allows the transverse movement of the apparatus 12.

The apparatus 12 further comprises a high-speed rotatable brush 80, mounted on an axle 82 which is driven by a motor 84 via a belt 86 - or other known means. The arrangement can be designed such that the brush 80, comprising bristles 88, can be rotated in either direction, however it is typically more effective for the brush to rotate in the direction opposite that of the progress of the vehicle 10.

The pressure of the brush 80 on the road markings M could be defined simply by the stiffness of the bristles 88 of the brush 80. To this end, the brush 80 could comprise bristles 88 of any combination of different length, thickness, stiffness and material (as long as the bristles reasonable withstand the heat and wear) to thereby optimize the pressure on the markings M and their removal.

However, to control and even out the pressure of the brush 80 on the road markings M, other means such as a spring (not shown) biased to press downward with a desired pressure or a weight (not shown) may be associated with the brush.

It should be understood that the bristles 88 of the brush 80 are configured in a pattern such that they contact the road markings M throughout the area of the markings, and to this end, groups of bristles may be shifted, offset, irregularly arranged, etc. For sake of clarity, this is not depicted in the figures.

The operation of the apparatus 12 for removing road markings M is as follows:

First, the truck 10 is driven to the location where erasure of road markings M is desired and it is positioned in alignment therewith. Due to the transverse displacement arrangement as explained above (using the spindle 20), it is not

- 6 -

mandatory that the truck **10** itself be centered on the markings **M**, rather only the apparatus **12** - and in actuality the brush **80** - need be aligned with the road markings **M**. This feature allows removal/erasure of markings **M** adjacent the margins or shoulders of road lanes without driving with half the vehicle **10** off the road; and allows the removal of centrally located road markings without need to drive the vehicle in the center of the road **R** which would potentially block traffic.

Then, while the torches **51** are burning and the brush **80** is rotating, the vehicle **10** is slowly driven over the road markings **M** thereby removing them.

10       The heating of the road markings **M** by the torches **51** may be direct with the distance of the torches from the road markings being adjustable, as described above. The distance of the torches **51** from the road markings **M** can be used to adjust and optimize the heat applied to the markings.

15       However, the heating of the road markings **M** may be indirect, for example by means depicted in Figs. 5 and 6 (where reference numerals similar to those of Figs. 1-4 have been used but with the numeral "1" preceding).

As seen in Figs. 5 and 6, the location and mode of operation of the brush **180** remains unchanged. However, the heating source **150** with torches **151** now corresponds with the brush **180** such that the heat is applied to the bristles **188** of the brush **180**. The torches **151** are preferably at an angle to the bristles **188**, as seen in Fig. 5. This has the effect of improving the heat transfer to the bristles **188** as well as avoiding excessive heating of the hub of the brush **180**.

Hence, now it is the heated bristles **188** that heat the road markings **M** and together with rotation of the brush **180** remove the markings. Thus, the only portion of the road **R** that is significantly heated is that portion contacted by the brush **180** - presumably just the road markings **M**.

The heating source **150** is again displaceable by an arrangement comprising, for example, a pneumatic cylinder **152**, a piston **154**, and supporting rollers **158** and **160** for adjusting the amount of heat applied to the brush **180**.  
30   Examples of alternate arrangements for displacing the heating source **50**, **150**

- 7 -

include a threaded spindle (like spindle 20), a gear mechanism, extending-retracting scissor-like rods, a lever system, and the like.

One example of a modification of the above embodiments includes the use of extra brushes (not shown) - potentially each brush having its own heating source. These brushes may spin in opposite directions to thereby improve removal of the markings removal on uneven roads. In a further option, the brush 80, 180 or brushes just referred to may be rotatable at different rpm, and have bristles 88, 188 of different characteristics, e.g. lengths, thicknesses, materials, etc.

Another example of a modification of the above embodiments includes the use of extra heating sources (not shown); e.g. an arrangement wherein both the road R and brush 80, 180 - or brushes - are heated.

Yet another example of a modification of the above embodiments includes the use of an additional heating source, or "branch" of the existing heating source (not shown) disposed at the back side of the brush 80, 180. It may happen that some amount of material composing the road markings M may stick to the brush bristles 88. This added heating source may improve removal of road markings material from the brush 80, 180, if any sticks thereto. In the embodiment where the brush 180 is heated by the heating source 150 (Figs. 5 and 6), that heating source may be sufficient to maintain the cleanliness of the brush bristles 188.

Furthermore, as the road markings M may be composed of various materials and thicknesses, it may be desirable to have available brushes 80, 180 of different characteristics. This can be accomplished, for example, by having more than one brush type installed in the apparatus 12 adaptable to position the appropriate brush adjacent the road markings M or adapting the brushes to allow quick change-out thereof.

Those skilled in the art to which this invention pertains will readily appreciate that numerous changes, variations and modifications can be effectuated without departing from the true spirit and scope of the invention as defined in and by the appended claims.



**CLAIMS:**

1. An apparatus for erasing a road marking on a road lane comprising:
  - a chassis adapted to travel over said road lane;
  - 5 - a heating source mounted to the chassis for directly or indirectly applying heat to the road marking; and
  - a positively driven rotatable brush mounted to said chassis, said brush having bristles contactable with said road marking and adapted for removing the marking,
  - 10 when heated, from said road.
2. The apparatus of Claim 1, wherein the heating source is directed toward the road marking.
3. The apparatus of Claim 1, wherein the heating source is directed toward the bristles of the brush which are adapted to heat the road marking.
- 15 4. The apparatus of Claim 1, wherein the heating source is adapted to directly heat the road marking and the bristles of the brush.
5. The apparatus of Claim 1, wherein the heating source comprises fuel torches.
6. The apparatus of Claim 1, wherein the heating source comprises an  
20 electric heater.
7. The apparatus of Claim 1, wherein the heating source is adjustable to a variety of distances from the road marking or from the bristles of the brush.
8. The apparatus of Claim 7, wherein the distance is controllable via a means comprising a pneumatic cylinder and a piston assembly.
- 25 9. The apparatus of Claim 1, wherein the chassis is adapted for attaching to the front of a vehicle.
10. The apparatus of Claim 9, wherein the chassis is displaceable in a direction transverse to the vehicle.

– 9 –

11. The apparatus of Claim 10, wherein the chassis is mounted on and coupled to a screw-threaded spindle, means being provided for rotating the spindle thereby attaining the transverse displacement thereof.

12. The apparatus of Claim 9, wherein the chassis is supported by the  
5 vehicle.

13. The apparatus of Claim 1, wherein said apparatus further comprises wheels for supporting the weight thereof.

14. The apparatus of Claim 4, wherein the torches are provided on a multi-flame support burner unit, the unit being mounted to the chassis by vertically  
10 adjustable means.

15. The apparatus of Claim 14, wherein the burner unit is supported by vertical guide rails.

16. The apparatus of Claim 4, wherein a chimney is provided for removing combustion gases.

15 17. The apparatus of Claim 1, wherein the bristles of the brush are contactable with the road marking with a pressure determined by one or more springs associated with the brush.

18. The apparatus of Claim 1, wherein the bristles of the brush are contactable with the road marking with a pressure determined by an auxiliary  
20 weight associated with the brush.

19. The apparatus of Claim 1, wherein the brush is replaceable.

20. The apparatus of Claim 1, wherein the apparatus comprises multiple brushes.

21. The apparatus of Claim 20, wherein at least one of the brushes comprises  
25 bristles having characteristics different than those of the bristles of other brushes.

22. The apparatus of Claim 20, wherein brushes are caused to spin in opposing directions.

23. The apparatus of Claim 20, wherein the apparatus is adapted to cause some or all of the brushes to be in contact, or be removed from contact, with the  
30 road marking.

– 10 –

**24.** A method for erasing a road marking on a road lane comprising:

- providing an apparatus comprising a chassis having mounted thereto a heating source and a rotatable brush with bristles;
- bringing said apparatus to the road lane;
- 5 - causing said chassis to travel over said road lane;
- applying heat directly or indirectly to the road marking; and
- causing bristles of said brush to rotate and contact the road marking thereby removing the marking.

**25.** A method according to claim **24**, wherein applying heat indirectly to the  
10 road marking comprises heating the bristles of the brush which are adapted to heat the road marking.

1/4




FIG. 1

2/4




FIG. 2

3/4




FIG. 4




FIG. 3




FIG. 5




FIG. 6

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/IL 03/00690

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E01C23/088 E01C23/14 E01C23/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E01C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 26 50 487 A (WIRTGEN REINHARD) 11 May 1978 (1978-05-11)	1, 2, 5-8, 13-15, 24
Y	the whole document	3, 4, 9-12, 16-18, 20, 23, 25
Y	DE 31 40 984 A (WUERFEL WOLFGANG) 26 May 1983 (1983-05-26)	3, 4, 25
Y	US 5 382 084 A (DIVER DAVID R ET AL) 17 January 1995 (1995-01-17)	10, 11
	column 7, line 54-65 figures 1, 2	
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

13 November 2003

Date of mailing of the international search report

27/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Kerouach, M



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/IL 03/00690

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 935 027 A (HAASTEREN ANDREAS GIJSBERTUS V) 11 August 1999 (1999-08-11) column 3, line 27-35 claim 5 ----	17, 18
Y	DE 28 52 218 A (WIRTGEN REINHARD) 19 June 1980 (1980-06-19) page 5, paragraph 1; figure 1 ----	9, 12
A	US 6 174 104 B1 (FIELDS DOUGLAS J) 16 January 2001 (2001-01-16) column 3, line 7-42; figure 3 ----	10
Y	US 3 013 552 A (CHARLES WEST FREDERICK) 19 December 1961 (1961-12-19) column 3, line 3-7 ----	16
Y	DE 28 47 924 A (WIRTGEN REINHARD) 14 May 1980 (1980-05-14) figure 1 -----	20, 23

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/IL 03/00690

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 2650487	A	11-05-1978	DE 2650487 A1	11-05-1978
DE 3140984	A	26-05-1983	DE 3140984 A1	26-05-1983
US 5382084	A	17-01-1995	AU 7372094 A WO 9504191 A1	28-02-1995 09-02-1995
EP 0935027	A	11-08-1999	NL 1008211 C2 EP 0935027 A2	06-08-1999 11-08-1999
DE 2852218	A	19-06-1980	DE 2852218 A1	19-06-1980
US 6174104	B1	16-01-2001	NONE	
US 3013552	A	19-12-1961	NONE	
DE 2847924	A	14-05-1980	DE 2847924 A1	14-05-1980